AGILE

Quality and Finish	**Agile with REPEL+**	
Colour	**Dark Navy, Gold, Flame Red**	
Composition	**59.3% Meta Aramid 39.4% Para Aramid 1.3% Antistatic**	
Construction	**Gabardine Weave**	
Conditioned Weight (gsm)	**180 +/- 5%**	**BS EN12127**
Useable Width (cms)	**≥ 160**	**BS EN 1773:1997**
Tensile Strength Warp / Weft (N)	**≥ 1300 / 2500**	**BS EN ISO 13934-1**
Tensile Extension Warp / Weft (%)	**≥ 43 / 4.0**	**BS EN ISO 13934-1**
Tear Strength Warp / Weft (N)	**≥ 90 / 160**	**BS EN ISO 13937-2**
Washing Stability Warp / Weft (%)	**≥ 2.4 / 0.6**	**ISO 5077 after 5 cycle to ISO 6330 (2A Pro E)**
Heat Resistance 180°C (%)	**< 5%**	**EN ISO 17493**
Abrasion Resistance 12KPa 2 Broken Threads	**≥ 100,000**	**ISO 12947-2**
Water Repellency	**≥ 5**	**BS EN ISO 4920**
Resistance to Penetration by Liquid Chemicals	**≥ 80% washes (91%)**	**BS EN ISO 6530**
After Care	**Wash at 60C Tumble Dry Hot - Do not bleach**	

HAINSWORTH®
PROTECTIVE FABRICS

Spring Valley Mills, Stanningley, Pudsey, West Yorkshire LS28 6DW United Kingdom

hainsworthprotectives.co.uk

ISO 9001 CERTIFICATION™ Intertek
UKAS MANAGEMENT SYSTEMS 014