

# ECO-DRY ACTIVE

Quality and Finish	<b>Hainsworth® Eco Dry Active</b>	
Colour	<b>Paris / Ecreu</b>	
Composition	<b>46% Nomex® 54% Wool/Lenzing</b>	
Construction	<b>Double Cloth</b>	
Conditioned Weight (gsm)	<b>220 +/- 5%</b>	<b>BS EN12127</b>
Useable Width (cms)	<b>≥ 158</b>	<b>BS EN 1773:1997</b>
Tensile Strength Warp / Weft N	<b>≥ 700 / 600</b>	<b>BS EN ISO 13934-1</b>
Tensile Extension Warp / Weft %	<b>≥ 13 / 14</b>	<b>BS EN ISO 13934-1</b>
Tear Strength Warp / Weft N	<b>≥ 70 / 75</b>	<b>BS EN ISO 13937-2</b>
Washing Stability Warp / Weft %	<b>≤ 3</b>	<b>ISO 5077 after 5 cycles To ISO 6330 (2A Pro E)</b>
Abrasion Resistance 12KPa 2 Broken Threads	<b>≥ 50,000</b>	<b>ISO 12947-2</b>
Pilling	<b>≥ 3-4</b>	<b>BS EN ISO 12945-2 4000 Cycles</b>
Colour Fastness to Light	<b>≥ 3</b>	<b>BS EN ISO 105 B02</b>
Water Repellency	<b>&gt; 4</b>	<b>EN 24920</b>
After Care	<b>Wash at 60C Tumble Dry Hot - Do not bleach</b>	



**HAINSWORTH®**  
**PROTECTIVE FABRICS**

Spring Valley Mills, Stanningley, Pudsey, West Yorkshire LS28 6DW United Kingdom

**[hainsworthprotectives.co.uk](http://hainsworthprotectives.co.uk)**

