

TITAN 1260

Uses	Outer Shell - Firefighter	
Quality and Finish	TITAN 1260 Repel+	
Colour	Black and Gold	
Composition	45% Para-aramid 23% Meta-aramid 30% PBI 2% Antistatic	
Construction	Plain Weave Rip Stop	
Conditioned Weight gsm	220 +/- 5%	BS EN12127
Useable Width cms	≥ 160	BS EN 1773:1997
Tensile Strength Warp / Weft N	≥ 2000 / 2000	BS EN ISO 13934-1
Tensile Extension Warp / Weft %	≥ 18 / 7	BS EN ISO 13934-1
Tear Strength Warp / Weft N	≥ 165 / 165	BS EN ISO 13937-2
Washing Stability Warp / Weft %	≤ 3	ISO 5077 after 5 cycles To ISO 6330 (2A Pro E)
Abrasion Resistance 12KPa 2 Broken Threads	≥ 30,000	ISO 12947-2
Pilling	≥ 4	BS EN ISO 12945-2 4000 Cycles
Flammability: Limited Flame Spread	Index 3	EN ISO 15025 Method A
Colour Fastness to Light	≥ 5	BS EN ISO 105 B02
Water Repellency	> 4	EN 24920
After Care	Wash at 60C Tumble Dry Hot - Do not bleach	

*Technical Specifications above relate to TITAN 1260 Black Gold, specific details for other colours of TITAN 1260 are available on request from sales@hainsworthprotectives.co.uk.



HAINSWORTH[®]
PROTECTIVE FABRICS

Spring Valley Mills, Stanningley, Pudsey, West Yorkshire LS28 6DW United Kingdom

hainsworthprotectives.co.uk

